

2810

Powerful and stable



HIGHLIGHTS AT A GLANCE:

- up to 800 characters / sec.
- up to 50,000 pages / month
- long-lasting printhead
- up to 6 copies
- industrial housing
- Metal tear-off edge
- Ethernet interface with IPv6 support
- Coax interface with IPDS support

2810

The 2810 printers are rugged and powerful high speed matrix printers for heavy duty operation under the most extreme conditions. Reliable, heavy workload output is guaranteed for many years following printer purchase. The print is crisp, sharp, dark and absolutely legible, thanks to the 24 pin print head.

Low running costs and durability in the harshest of print environments make these products excellent value for money.

These products are well matched to Microsoft Windows applications, and highly compatible with other host operation environments including legacy systems. Fully automated operation, coupled with the 'straight through' paper path, allows ease of use and virtually eliminates errors caused by user intervention.

TECHNICAL DATA

Print Speed	800 cps (High Speed), 667 cps (Data Print), 222 cps (NLQ) at 10 cpi
Resolution	up to 360 x 360 dpi
Throughput (ECMA 132)	640 pages per hour
Character Density	5, 6, 7.5, 8.6, 10, 12, 15, 17.1, 20 cpi
Line Density	2, 3, 4, 6, 8, 12 lpi
Print Head Life	750 million characters
Memory	256 kB
Standard Connectivity	USB 2.0 (Full Speed) and Ethernet 10/100Base with IPv6 support, USB Host
Optional Connectivity	Parallel IEEE 1285 and Serial RS232 combo interface / Ethernet Multi-protocol, Ethernet with SCS or IPDS support / Coax with SCS or IPDS support
Standard Emulation	IBM ProPrinter XL24e, Epson LQ (ESC P/2), MTPL, Genicom ANSI + Barcode + LCP
Fonts	Data Print Quality, Roman, Sans Serif, Courier, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 17 bar-codes and large character printing
Consumables	Ribbon: 20 million characters
Administration	Backlit Panel, internal web page, System settings/firmware upload via USB Host interface
Standard Paper Handling	Push tractor for continuous paper with straight paper path, tear off and park position
Optional Paper Handling	Additional push tractor (front), Automatic cutting device
Number of Copies	Push tractor front: 1 original + 6 copies
Paper Type	Continuous forms, multi-part forms
Paper Weight	60-120 g/m ²
Paper Size	Width: 76 to 420 mm; Length: 76 to 559 mm
Physical Weight	19 kg
Physical Size	624 x 432 x 280 mm (W x D x H)
Acoustic	54 dB(A)
Power Voltage	230 V - 50/60 Hz
Power Consumption	75 Watt Printing; 2 Watt Power Save
Temperature	+10° to +35° C; 15% to 75% humidity
Workload	50.000 pages per month
MTBF	20.000 hours
Drivers	Windows 8/10 (32 and 64 bit) and Server 2012/2016; SAP

Configurations:

- 2810 Standard model

DASCOM GB Ltd

Hart House, Priestley Road
Basingstoke | Hampshire RG24 9PU | ENGLAND
Tel.: +44 1256 355 130 | Fax: +44 1256 481 400
info.gb@dascom-com | www.dascom.co.uk

DASCOM Europe GmbH

Heuweg 3 | 89079 Ulm | GERMANY
Tel.: +49 731 2075-0 | Fax: +49 731 2075-100
info@dascom.com | www.dascomeurope.de

DASCOM (Holdings) LTD.

R. 1811-1816A | Nan Fung Centre
264-298 Castle Peak Road | Tuen Wan, N. T. | Hong Kong
Tel.: +852 2498 1507 | Fax: +852 2413 6047