

## T5040



*Tally*

With up to 600 characters per second, the T5040 rapidly processes media of diverse types ranging from passbooks and cheques to A5 receipts and A4 information sheets.

The printer's flatbed design provides totally assured paper handling, and with advanced features such as Automatic Paper Alignment and Auto Gap Adjustment (AGA), they offer unsurpassed ease-of-use. Using Serial Impact technology - the most reliable and versatile method available of producing print - the T5040 is a durable, robust, dependable printer that supports a wide range of printing applications.

### Highlights at a glance:

- Supports a wide variety of media
- Automatic gap adjustment of the print head
- Automatic alignment of forms and passbooks
- Automatic edge detection
- Ability to connect to multiple hosts simultaneously via parallel, serial or USB
- Unrivalled transaction times - typical passbook 2.2 seconds, DIN Letter 11.8 seconds
- Large 256 KBytes buffer

The standard T5040 supports cut forms via a serial interface connection and a secure command language, as demanded within the banking environment. As standard, USB and Parallel interfaces are also included for flexibility of connection and multi-user operation. An alternative configuration with a second serial interface is available.

Also available are models with Magnetic Stripe encoding for reading accounts codes directly into the system minimizing user intervention.

Available Configurations:

- **T5040 Standard**
- **T5040 2 Serial**
- **T5040 MSR-H**
- **T5040 MSR-H + 2 Serial**

## T5040

<b>Print Speed</b>	600 cps (Fastest Mode); 400 cps (Draft), 133 cps (LQ) at 10 cpi
<b>Resolution</b>	up to 360 x 360 dpi
<b>Character Density</b>	10, 12, 15, 16.6, 17.1, 20 cpi
<b>Line Density</b>	1, 2, 3, 4, 6, 8 lpi
<b>Printhead</b>	24-pin, 400 million characters
<b>Memory</b>	256 KBytes
<b>Standard Connectivity</b>	Parallel (Bi-directional), Serial RS-232 and USB 2.0. Optional 2nd Serial.
<b>Standard Emulation</b>	IBM 4722, IBM ProPrinter XL24E, Epson LQ (ESC P/2), Olivetti PR50/PR2/PR2e
<b>Fonts</b>	Draft, Courier, Roman, Sans Serif, Prestige, Script, Orator, Gothic, Souvenir, OCR-A/B, 10 Barcodes
<b>Consumables</b>	Ribbon: 10 million characters
<b>Standard Paper Handling</b>	Cut sheet: Front with auto align, auto load, auto edge & gap detections
<b>Number of Copies</b>	1 original + 6 copies *
<b>Paper Type</b>	Cut sheets, multi-part forms, passbooks with a thickness up to 2.0 mm
<b>Paper Weight</b>	60 - 260 g/m <sup>2</sup>
<b>Paper Size</b>	Width: 70 to 240 mm; Length: 70 to 500 mm (cut sheet) Width: 105 to 235 mm; Length: 125 to 210 (passbooks)
<b>Physical Weight</b>	< 10 kg
<b>Physical Size</b>	378 x 280 x 168 mm (W x D x H)
<b>Acoustic</b>	55 dB(A)
<b>Power Voltage</b>	230 V - 50/60 Hz
<b>Power Consumption</b>	73 W Printing; 9 Watt Stand-By
<b>Temperature</b>	+10° to +40° C; 15% to 75% humidity
<b>Workload</b>	5,000 transactions per month
<b>MTBF</b>	10,000 hours
<b>Drivers</b>	Windows 2000/XP/Vista/7/Server 2003/2008
<b>Standard Warranty</b>	One Year with Printhead inclusive

\* Performance may vary subjected to media use