

DL-200 Thermal Label Printer



Tally
DASCOM

Tally Dascom's DL-200 thermal transfer printer offers reliability, precision and performance in desktop size.

The user friendly design of the printer allows a space saving vertical opening and an easy to use printer mechanism ensures quick media and ribbon loading. The clear panel enable simple and effective operation making it very simple to use.

Highlights at a glance:

- 5 inches / sec speed printing
- Easy ribbon and paper loading
- Small, compact footprint
- Supports a variety of interfaces
- Supports ZPL, EPL and TSC emulations
- Optional cutter, peeler, large paper roll support

The DL-200 is easily integrated into existing systems as it supports a wide variety of interfaces. In addition to this, the DL-200 is also available with an optional cutter or peeler to meet the various requirements.

Configurations:

- Standard Product (USB only)
- Printer with Parallel / Serial / WIFI / Ethernet / Bluetooth interface option
- Printer with cutter
- Printer with peeler
- Printer with large paper roll support

DL-200

Print Speed	5 ips (127 mm/sec)
Print Width	4"/ 108 mm
Print Method	Direct Thermal or Thermal Transfer
Print Head Lifetime	30 km or 6 months whichever is earlier
Resolution	203 dpi
Fonts	Font A - Font V (ZPL) User defined fonts can be downloaded into FLASH/SDRAM
Memory	8 MB SDRAM; 8 MB Flash
Interface	USB (2.0 Full Speed)
Interface Options	Serial (RS-232C), Parallel (IEEE-1284), Ethernet, WIFI, Bluetooth
Emulations	ZPL, EPL, TSC
Ribbon	Width: 30 - 110 mm; Length: 74 m Core diameter: 12.7 mm; Outside diameter: 35 mm
Media	Width: 25.4 - 120 mm; Thickness: 0.05 - 0.32 mm Core diameter: 25.4 / 38.1 mm; Outside diameter: 127 mm (Large Roll model: 160 mm)
Media Type	Thermal paper, media, black mark paper
Sensors	Paper detection sensor; Black mark sensor, Label gap sensor, Ribbon sensor, Mechanical sensor Optional: paper taken sensor
Barcode	1D: Code 39, UPC-A, UPC-E, Matrix 25, Industrial 2 of 5, Interleaved 2 of 5, Post 2 of 5, Code 128, EAN-8, EAN-13, HBIC (Code 39), Codabar, UPC-2, UPC-5, Code 93 2D: PDF 417, MaxiCode, QR Code, Data MatrixR
Physical Weight	1.85 kg
Physical Size	173 x 207 x 241 mm (H x W x D) / Large Roll model: 208 x 207 x 278 (H x W x D)
Power Voltage	100-240 V AC, 50-60Hz
Printer Driver	Windows (32/64 Bit)
Temperature	Operating: 5° C - 40° C
Humidity	Operating: 20% - 95% (not-condensing)
Acoustic	< 55 dB(A)
Options	Cutter, Peeler, Large Roll Model

DASCOM AP Pte Ltd

21 Bukit Batok Crescent

#29-81 WCEGA Tower

Singapore 658065

Tel: +65 6760 8833 – Fax: +65 67601066

sales@dascom.com.sg – www.dascom.com.sg

SERIAL MATRIX PRINTERS 

MOBILE PRINTERS 

FLATBED PRINTERS 

THERMAL PRINTERS 