

DP-330 Mobile Printer



Highlights at a glance:

- Easy-to-read control panel and simple drop-in paper loading
- Easy configuration via browser
- High-speed printing and extensive font and graphic capabilities
- Rugged, industrial design
- Long battery life to last the whole day under normal usage

Reliable Printing

Built to survive the real world: drop it on a concrete warehouse floor, shake it as your truck hits pothole after pothole, carry it from the truck in a rainstorm, and watch as the DP-330 just keeps on printing.

Provides the Connectivity and Compatibility You Need

If it's a wired or wireless connection you need, the DP-330 is capable of both. With USB, Bluetooth or WiFi, the choices available are sure to fit your requirement.

Ease of Use

The angled LED provides human readable messages that are easy to understand, and the control panel buttons are clearly marked. Paper loading is drop in and receipts are easy to tear off as they are printed.

Configuring the printer is as easy as connecting it to your desktop browser.

Configurations:

- **DP-330** Standard model
- **DP-330 BT** Model with Bluetooth
- **DP-330 WiFi** Model with WiFi

DP-330

Print Method	Direct thermal printing
Resolution	203 dpi (8 Dots/mm)
Print Speed	Up to 5 inches/sec.
Barcodes	1D and 2D barcodes
Download	Graphics and logos
Standard Connectivity	USB 2.0
Optional Connectivity	Bluetooth (4.0) and WiFi (802.11 b/g/n)
Bluetooth	Complete Bluetooth 4.0 Stack Protocols: L2CAP, RFCOMM, SDP Profiles: GAP, SDAP, SPP, BTLE
Emulations	JPL, ESC/POS
Printer Drivers	Windows; SDK for Windows CE/Mobile, Android and iOS
Paper Roll Size	Max. diameter 2" (50 mm); Width 2.26 to 3.125" (57 to 80 mm)
Paper Roll Capacity	Approx. 28.6m (equivalent 188 pcs 6" receipts)
Paper Core Diameter	0.75" (19 mm)
Battery	Rechargeable 3-cell Lithium Ion (2950 mAH)
Battery Lifetime	400 m @ 12.5% print density
Charging Time	2 to 4 hours
Weight	0.57 kg incl. battery
Dimensions	125 x 168 x 71 mm (W x D x H)
Power Voltage	19 V
Temperature	-10° C to 45° C (operating), -25° C to 65° C (storing)
Humidity	0% to 65% (operating), 0% to 98% (storing)
MTBF	10,000 hours
Approvals	CCC, CE
Durability	Rated IP54, 1.8 m drop test
Options & Accessories	In Vehicle Adapter, AC Adapter, Shoulder Strap

DASCOM AP Pte Ltd

2 Jurong East Street 21

#05-42 IMM BUILDING, Singapore 609601

Tel: +65 6760 8833 – Fax: +65 6760 1066

sales@dascom.com.sg – www.dascom.com.sg

SERIAL DOT MATRIX PRINTER

MOBILE PRINTER

FLATBED PRINTER

THERMAL PRINTER