

## DP-530L



### Highlights at a glance:

- Easy-to-read control panel and simple drop-in paper loading
- Prints a wide variety of labels, tickets, and receipts
- High-speed printing and extensive font and graphic capabilities
- Compatible with popular printer emulations
- IP54 rated for water and dust resistant; rated for 1.8m drops
- Long battery life

### Light, Fast, and Rugged

The DP-530L is compact, lightweight, extremely fast, and your best choice for 3" (80mm) label and receipt printing. It helps to improve operations and productivity throughout the warehouse, retail sales floor, on the road, or at a customer site.

### Reliable Printing

Built to survive the real world: drop it on a concrete warehouse floor, shake it as your truck hits pothole after pothole, carry it from the truck in a rainstorm, and watch as the DP-530L just keeps on printing.

### Ease of Use

The angled LED provides human readable messages that are easy to understand, and the control panel buttons are clearly marked. Paper loading is drop in and receipts are easy to tear off as they are printed.

### Provides the Connectivity and Compatibility

Whether it's a wired or wireless connection you need, the DP-530L is capable of both. With USB, Bluetooth or WiFi, the choices available are sure to fit your requirement.

The DP-530L supports a variety of emulations that allows it to be a drop-in replacement for most mobile printers.

### Available Configurations

- **DP-530L**            USB
- **DP-530L BT**     USB + Bluetooth
- **DP-530L WIFI**    USB + WIFI

## DP-530L

<b>Print Method</b>	Direct thermal printing
<b>Resolution</b>	203 dpi (8 Dots/mm)
<b>Print Speed</b>	Up to 5.5 inch/sec.
<b>Barcodes</b>	Virtually all 1D and 2D barcodes supported, depending on emulation chosen
<b>Download</b>	Graphics , fonts, and logos
<b>Memory</b>	256 MB Flash, 512 MB RAM
<b>Standard Connectivity</b>	USB 2.0
<b>Optional Connectivity</b>	Bluetooth (4.0) Dual Mode with EDR, and WiFi (802.11 b/g/n)
<b>Bluetooth</b>	Complete Bluetooth 4.0 Stack Protocols: L2CAP, RFCOMM, SDP Profiles: GAP, SDAP, SPP, BTLE
<b>Emulations</b>	Zebra CPCL and ZPL, ESC/POS, Printek, Exttech, IPL, Postscript, PDF, JPG, BMP, TIFF, PNG
<b>Printer Drivers</b>	Windows; SDK for Windows CE/Mobile, Android and iOS
<b>Paper Roll Size</b>	Max. diameter 2.625" (66.7 mm); Width 2.26 to 3.125" (57 to 80 mm)
<b>Paper Roll Capacity</b>	Receipt: ~52.6 m, Labels: ~23 m
<b>Paper Core Diameter</b>	0.75" (19 mm)
<b>Battery</b>	Rechargeable 3-cell Lithium Ion (2950 mAH)
<b>Battery Lifetime</b>	More than 3500" (89 m) / 8 hours shift without WiFi
<b>Charging Time</b>	2 hours
<b>Weight</b>	0.68 kg incl. battery
<b>Dimensions</b>	125 x 168 x 79 mm (W x D x H)
<b>Power Voltage</b>	100-240 VAC, 12/24 VDC
<b>Temperature</b>	-18° C to 50° C (operating), -20° C to 60° C (storing)
<b>Humidity</b>	10% to 90%
<b>MTBF</b>	10,000 hours
<b>Approvals</b>	CE, FCC Class B, UL, RoHS
<b>Durability</b>	Rated IP54, 1.8 m drop test
<b>Options &amp; Accessories</b>	In Vehicle Adapter, AC Adapter, Shoulder Strap

### DASCOM AP Pte Ltd

2 Jurong East Street 21

#05-42 IMM BUILDING, Singapore 609601

Tel: +65 6760 8833 – Fax: +65 6760 1066

sales@dascom.com.sg – www.dascom.com.sg

SERIAL DOT MATRIX PRINTER

MOBILE PRINTER

FLATBED PRINTER

THERMAL PRINTER