

# DP-530



### Reliable Printing

Built to survive the real world: drop it on a concrete warehouse floor, shake it as your truck hits pothole after pothole, carry it from the truck in a rainstorm, and watch as the DP-530 just keeps on printing.

### Provides the Connectivity and Compatibility You Need

If its a wired or wireless connection you need, the DP-530 is capable of both. With USB, RS232 serial, Bluetooth and WiFi, the choices available are sure to fit your requirement.

### Highlights at a glance:

- Easy-to-read control panel and simple drop-in paper loading
- Simple drop-in paper loading
- High-speed signature printing and extensive font and graphic capabilities
- Popular printer emulations provide compatibility

### Ease of Use

The angled LCD provides human readable messages that are easy to understand, and the control panel buttons are clearly marked. Paper loading is drop in and receipts are easy to tear off as they are printed.


#### Configurations:

- **DP-530** Standard model
- **DP-530 BT** Model with Bluetooth
- **DP-530 WiFi** Model with WiFi

## DP-530

<b>Print Method</b>	Direct thermal printing
<b>Resolution</b>	203 dpi (8 Dots/mm)
<b>Print Speed</b>	Up to 5 inch/sec.
<b>Barcodes</b>	82 different versions
<b>Download</b>	Graphics and logos
<b>Standard Connectivity</b>	USB
<b>Optional Connectivity</b>	IrDA, Bluetooth (2.0) and WiFi (802.11 b/g/n)
<b>Bluetooth</b>	Compatible Bluetooth 2.0 Stack Protocols: L2CAP, RFCOMM, SDP Profile: GAP, SDAP, SPP, BTLE
<b>Emulations</b>	Zebra CPCP and ZPL, EPL, ESC/POS, O'Neil, Printek
<b>Printer Drivers</b>	Windows 7/8; SDK for Windows CE/Mobile, Android and iOS
<b>Printer Roll Size</b>	max. diameter 2" (5 cm); Width 2,26 to 3,125" (5,7 to 8,0 cm)
<b>Roll Capacity</b>	approx. 57 m (equal 372 pcs. 6"-labels)
<b>Roll Diameter</b>	0,75" (1,9 cm)
<b>Battery</b>	Rechargeable 3-cell Lithium Ion (2.950 mAH)
<b>Battery lifetime</b>	More than 4.000" (101 m) /8 hours shift without WiFi
<b>Charging</b>	2 hours
<b>Weight</b>	0,57 kg incl. battery
<b>Dimensions</b>	125 x 168 x 71 mm (W x D x H)
<b>Power Voltage</b>	112/24 V
<b>Temperature</b>	-20° C to 50° C (operating), -20° C to 60° C (storing)
<b>Humidity</b>	10% to 90%
<b>MTBF</b>	10.000 hours
<b>Approvals</b>	CE, FCC Class B, UL, RoHSL
<b>Options &amp; Accessories</b>	In Vehicle Adapter, AC Adapter, Shoulder Strap

**DASCOM AP Pte Ltd**  
 2 Jurong East Street 21  
 #05-42 IMM BUILDING, Singapore 609601  
 Tel: +65 6760 8833 – Fax: +65 6760 1066  
 sales@dascom.com.sg – www.dascom.com.sg

SERIAL DOT MATRIX PRINTER   
 MOBILE PRINTER   
 FLATBED PRINTER   
 THERMAL PRINTER 